


CLAIMS

1. A fluororesin composition comprising a fluorine-containing ethylenic polymer and a carbon fibril,
5 wherein said fluorine-containing ethylenic polymer is a carbonyl group-containing one and said carbon fibril amounts to 0.3 to 20% by mass relative to the total solid matter of said carbon fibril and said fluorine-containing ethylenic polymer.
- 10 2. The fluororesin composition according to Claim 1, wherein the number of carbonyl groups is 3 to 3,000 per 1 x 10⁶ main chain carbon atoms in the fluorine-containing ethylenic polymer.
- 15 3. The fluororesin composition according to Claim 1 or 2, wherein the fluorine-containing ethylenic polymer is a polymer having a tetrafluoroethylene unit content of not lower than 40 mole%.
- 20 4. The fluororesin composition according to Claim 1, 2 or 3, wherein the fluorine-containing ethylenic polymer is a copolymer comprising tetrafluoroethylene and a perfluoro 25 ethylenic monomer represented by the following general formula (I):
$$\text{CF}_2=\text{CF-Rf}^1 \quad (\text{I})$$
wherein Rf¹ represents -CF₃ or -ORf² and Rf² represents a perfluoroalkyl group containing 1 to 5 carbon atoms.
- 30 5. The fluororesin composition according to Claim 1 or 2, wherein the fluorine-containing ethylenic polymer is a copolymer comprising the following a, b and c:
 - a. 20 to 90 mole% of a tetrafluoroethylene unit,
 - 35 b. 10 to 80 mole% of an ethylene unit and

c. 0 to 70 mole% of a perfluoro ethylenic monomer unit derived from the perfluoro ethylenic monomer represented by the following general formula (I):



5 wherein Rf¹ represents -CF₃ or -ORf² and Rf² represents a perfluoroalkyl group containing 1 to 5 carbon atoms.

6. The fluororesin composition according to Claim 1 or 2, wherein the fluorine-containing ethylenic polymer is a
10 polymer having a vinylidene fluoride unit content of not lower than 15 mole%.

7. The fluororesin composition according to Claim 6, wherein the fluorine-containing ethylenic polymer is a
15 copolymer comprising the following d, e and f:

- d. 15 to 60 mole% of the vinylidene fluoride unit,
- e. 35 to 80 mole% of a tetrafluoroethylene unit and
- f. 5 to 30 mole% of a hexafluoropropylene unit.

20 8. The fluororesin composition according to Claim 1, 2,
3, 4, 5, 6 or 7,
wherein the carbon fibril comprises a fibrous matter having
an outside diameter of 1 to 1,000 nm and a length (L) in
the longitudinal direction-to-outside diameter (D) ratio
25 (L/D) over 5.

9. The fluororesin composition according to Claim 1, 2,
3, 4, 5, 6, 7 or 8,
wherein the carbon fibril comprises a carbon fibril
30 flocculate.

10. The fluororesin composition according to Claim 9,
wherein the carbon fibril flocculate has an average
particle diameter of 0.01 to 0.25 mm.

11. The fluororesin composition according to Claim 1, 2,
3, 4, 5, 6, 7, 8, 9 or 10
which comprises an inorganic filler as well as the
fluorine-containing ethylenic polymer and the carbon fibril,
5 said inorganic filler amounting to 3 to 50% by mass of said
fluororesin composition.
12. A fluorine-containing molded article
which comprises the fluororesin composition according to
10 Claim 1, 2, 3, 4, 5, 6, 7, 8, 9, 10 or 11.
13. A fluorine-based layer-containing laminate
which has a fluorine-based layer comprising the fluororesin
composition according to Claim 1, 2, 3, 4, 5, 6, 7, 8, 9,
15 10 or 11.
14. A method of using the fluorine-based layer-containing
laminate
which comprises using the fluorine-based layer-containing
20 laminate according to claim 13 in the presence of a liquid
chemical, said liquid chemical being contact with the
fluorine-based layer.
15. The fluorine-containing molded article according to
25 Claim 12 which is to be contact with a liquid when said
fluorine-containing molded article is used.
16. The fluorine-based layer-containing laminate
according to Claim 13,
30 wherein the fluorine-based layer is to be contact with a
liquid when said fluorine-based layer-containing laminate
is used.
17. The fluorine-containing molded article according to
35 Claim 12 or 15, which is a piping tube for coatings, a

transport tube for a drink and a liquid food, a chemical-transport tube or an auto fuel piping tube.

18. The fluorine-based layer-containing laminate
5 according to Claim 13 or 16, which is a piping tube for
coatings, a transport tube for a drink and a liquid food, a
chemical-transport tube or an auto fuel piping tube.